

## SAFETY DATA SHEET

### BT 200C GROUT

BuildTech Supplies Pty Ltd  
Version No: 1.10

Issue Date: Sept 2022

#### Section 1 MATERIAL AND SUPPLY COMPANY IDENTIFICATION

##### Product Identifier

Product Name	BT 200C GROUT
--------------	---------------

##### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified uses	High Strength Class C non shrink cementitious grout
--------------------------	---

##### Details of the supplier of the safety data sheet

Registered Company Name	Build Tech Supplies Pty Ltd
Address	34 Derwent Park Road , Derwent Park 7009 , TAS
Telephone	03 6273 5800
Website	<a href="http://www.buildtechsupplies.com.au">www.buildtechsupplies.com.au</a>
Email	<a href="mailto:admin@buildtechsupplies.com.au">admin@buildtechsupplies.com.au</a>

##### Emergency telephone number

Emergency Telephone Numbers	03 6273 5800
Other emergency telephone numbers	

## SECTION 2 HAZARDS IDENTIFICATION

##### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS.** According to the WHS Regulations and the ADG Code

Poisons Schedule	Not Applicable
Classification	Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Carcinogenicity Category 1A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - repeated exposure Category 2

##### Label elements

Hazard pictogram(s)	
---------------------	---

SIGNAL WORD	<b>DANGER</b>
-------------	---------------

##### Hazard statement(s)

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

H373	May cause damage to organs through prolonged or repeated exposure.
------	--

**Precautionary statement(s) Prevention**

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement(s) Response**

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P310	Immediately call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing and wash before reuse.

**Precautionary statement(s) Storage**

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container in accordance with local regulations.
------	---

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

**Substances**

See section below for composition of Mixtures

**Chemical Entity**

CAS No	%[weight]	Name
14808-60-7	30-60	Silica 100G
65997-15-1	30-60	Portland Cement

## SECTION 4 FIRST AID MEASURES

**Description of first aid measures**

<b>Eye Contact</b>	<p><b>If this product comes in contact with the eyes:</b>  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</p>
<b>Skin Contact</b>	<p>If skin contact occurs:  Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.</p>
<b>Inhalation</b>	<p><b>If fumes or combustion products are inhaled remove from</b> contaminated area. Lay patient down. Keep warm and rested.  Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.  Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.  Transport to hospital, or doctor, without delay.</p>
<b>Ingestion</b>	<p>If swallowed do <b>NOT</b> induce vomiting.  If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully.  Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.  Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</p>

	Seek medical advice.
--	----------------------

Indication of any immediate medical attention and special treatment needed – Treat symptomatically

## SECTION 5 FIREFIGHTING MEASURES

There is no restriction on the type of extinguisher which may be used. Use extinguisher suitable for surrounding area.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	None known.
-----------------------------	-------------

### Advice for firefighters

<b>Fire Fighting</b>	When Silica dust is dispersed in air, firefighters should wear inhalation protection as hazardous substances from the fire may be adsorbed on the Silica particles.
<b>Extinguishing Media</b>	When heated to extreme temperatures, (>1700 °C ) amorphous silica can fuse. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. Use water fog or fine water spray, standard foam, dry agent ( carbon dioxide, dry chemical powder)
<b>Fire/Explosion Hazard</b>	Non-combustible. Not considered a significant fire risk, however containers may burn. Silicon Dioxide (SiO <sub>2</sub> ) <ul style="list-style-type: none"> <li>• May emit poisonous fumes.</li> <li>• May emit corrosive fumes.</li> </ul>
<b>HAZCHEM</b>	Not Applicable

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

<b>Minor Spills</b>	Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance wear protective equipment.
<b>Major Spills</b>	Moderate hazard. <b>CAUTION:</b> Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
----------------------	--

<b>Other information</b>	Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.
--------------------------	--

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	Polyethylene or polypropylene container. Check all containers are clearly labelled and free from leaks.
---------------------------	--

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**CONTROL PARAMETERS**

**OCCUPATIONAL EXPOSURE LIMITS (OEL)**

Source	Ingredient	Material name	TWA	STEL
Australia Exposure Standards	Silica 100G	Silica - Quartz (respirable dust)/Quartz (respirable dust)	0.1 mg/m3	Not Available
Australia Exposure Standards	Portland Cement	Portland Cement	10 mg/m3	Not Available


**EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Silica 100g	Silica, Crystalline-Quartz; (Silicon Dioxide)	0.075 mg/m3	33 mg/m3	200 mg/m3

Ingredient	Original IDLH	Revised IDLH
Silica 100G	N.E. mg/m3 /N.E.ppm	50 mg/m3
Portland Cement	N.E. mg/m3 /N.E.ppm	5,000 mg/m3

**EXPOSURE CONTROLS**

<b>Appropriate engineering controls</b>	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
<b>Personal protection</b>	
<b>Eye and face protection</b>	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
<b>Skin protection</b>	See Hand protection below

<b>Hands/feet protection</b>	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances must be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Neoprene rubber gloves. Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present. Polychloroprene Nitrile rubber Butyl rubber.
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	Overalls P.V.C. apron Barrier cream
<b>Thermal hazards</b>	Not Available

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Fine grey powder; Partly mixes with water.		
<b>Physical state</b>	Divided Solid	<b>Relative density (Water = 1)</b>	1.5
<b>Odour</b>	Cementitious	<b>Partition coefficient n-octanol / water</b>	Not Available
		<b>Auto-ignition temperature (°C)</b>	Not Applicable
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Applicable
<b>Initial boiling point and boiling range (°C)</b>	Not Applicable		
<b>Flash point (°C)</b>	Not Applicable		
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Applicable		
<b>Lower Explosive Limit (%)</b>	Not Applicable	<b>Volatile Component (%vol)</b>	Not Available
<b>Solubility in water (g/L)</b>	Partly miscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	>1	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Chemical stability</b>	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
<b>Possibility of hazardous reactions</b>	No known of any hazardous reactions
<b>Conditions to avoid</b>	Elevated temperatures and sources of ignition
<b>Incompatible materials</b>	Oxidising agents
<b>Hazardous decomposition products</b>	Oxides of carbon and nitrogen, smoke and other toxic fumes

---

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

<b>Inhaled</b>	<p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of dusts, generated by the material during normal handling, may be damaging to the health of the individual. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.</p> <p>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures</p> <p>Effects on lungs are significantly enhanced in the presence of respirable particles.</p> <p>Acute silicosis occurs under conditions of extremely high silica dust exposure particularly when the particle size of the dust is small. The disease is rapidly progressive and spreads widely through the lungs within months of the initial exposure and causing death within 1 to 2 years.</p>
<b>Ingestion</b>	<p>Accidental ingestion of the material may be damaging to the health of the individual. Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.</p>
<b>Skin Contact</b>	<p>This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the bloodstream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
<b>Eye</b>	<p>If applied to the eyes, this material causes severe eye damage.</p>
<b>Chronic Toxicity</b>	<p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Harmful: danger of serious damage to health by prolonged exposure through inhalation.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Substance accumulation in the human body may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Cement contact dermatitis (CCD) may occur when contact shows an allergic response, which may progress to sensitisation. Sensitisation is due to soluble chromates (chromate compounds) present in trace amounts in some cements and cement products. Soluble chromates readily penetrate intact skin. Cement dermatitis can be characterised by fissures, eczematous rash, dystrophic nails and dry skin; acute contact with highly alkaline mixtures may cause localised necrosis.</p> <p>Crystalline silicas activate the inflammatory response of white blood cells after they injure the lung epithelium. Chronic exposure to crystalline silicas reduces lung capacity and predisposes to chest infections.</p> <p>Over exposure to respirable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity, chest infections.</p> <p>Repeated exposures in an occupational setting to high levels of fine divided dusts may produce a condition known as pneumoconiosis which is the lodgement of any inhaled dusts in the lung irrespective of the effect. This is particularly true when a significant number of particles less than 0.5 microns (1/50,000 inch) are present. Lung shadows are seen in the X-ray.</p>

---

## SECTION 12 ECOLOGICAL INFORMATION

Avoid contaminating waterways or sewer.

## SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

<b>Product / Packaging disposal</b>	<p><b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible or dispose of in an authorised landfill.</p>
-------------------------------------	---

## SECTION 14 TRANSPORT INFORMATION

### Labels Required

<b>Marine Pollutant</b>	No
<b>HAZCHEM</b>	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code is not applicable.

## SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture.

**SILICA 100G (14808-60-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

### Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) – Agents classified by the IARC Monographs

**PORTLAND CEMENT (65997-15-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Exposure Standards National Inventory	Australia Inventory of Chemical Substances (AICS) Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (Portland Cement; silica crystalline - quartz)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (Portland Cement; silica crystalline - quartz)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	N (Portland Cement)
USA - TSCA	Y
<b>Legend:</b>	<p>Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)</p>

---

## SECTION 16 OTHER INFORMATION

This Safety Data Sheet (SDS) summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage review the SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.